



Combination System

Water Maker + Purifier

FOR BOATS UP TO 400' | 122 m

One System. Every Drop Perfect.

A compact, fully automatic unit that combines a full-capacity seawater desalination system with an ultra-pure water purifier. It first converts seawater into fresh water, then refines it into a spot-free, contaminant-free finish — perfect for rinsing, cleaning, onboard living, and protecting your vessel.

bluelink[®] Connectivity

MFD & smart-device integration with over-the-air remote support & updates.

Two-in-One RO Design

One for sea, one for dock — combined and integrated.

Patented Doublepass Process

Eliminates pump cycling and TDS creep for longer lasting internals and stable pure water quality.

Water Source



Sea Water



Dock Water

Purity Level



Pure Water

The Next Generation

95% Plumbing Reduction

95 fewer connections for seamless, worry-free performance.

33% Smaller Footprint

Fits where others can't. Engineering to maximize utility space.

65% Quieter Operation

New low-vibration architecture. Designed to disappear.

Failsafe Design

Redundant systems and overrides ensure uninterrupted operation.





Combination System | Water Maker + Purifier

Technical Specs

Model Capacity Electrical Requirements

Water Purifier Total output from dock
Water Maker + Purifier Total output from sea

Gallons Per Hour | Liters Per Hour
Gallons Per Day | Liters Per Day

Combo 1200 1000	Water Purifier	42 GPH 159 LPH 1000 GPD 3785 LPD
	Water Maker + Purifier	28 GPH 106 LPH 667 GPD 2525 LPD
Combo 1200 2000	Water Purifier	83 GPH 314 LPH 2000 GPD 7570 LPD
	Water Maker + Purifier	28 GPH 106 LPH 667 GPD 2525 LPD
Combo 1800 2000	Water Purifier	83 GPH 314 LPH 2000 GPD 7570 LPD
	Water Maker + Purifier	53 GPH 200 LPH 1267 GPD 4796 LPD
Combo 2200 2000	Water Purifier	83 GPH 314 LPH 2000 GPD 7570 LPD
	Water Maker + Purifier	69 GPH 261 LPH 1667 GPD 6310 LPD
Combo 2200 3000	Water Purifier	125 GPH 473 LPH 3000 GPD 11356 LPD
	Water Maker + Purifier	69 GPH 261 LPH 1667 GPD 6310 LPD

Voltage

230 VAC

Max Amp Draw

At Sea - 19 A @ 230 V
At Marina - 5 A @ 230V

Frequency

50/60Hz

Phase

Single or Three Phase

System Components




Combo 1800 | 2000

L 21 in | 53.3 cm
D 13.5 in | 34.2 cm
H 25.75 in | 65.4 cm
Weight 205 lb | 93 kg



Fresh Water Membrane

L 48 in | 121.9 cm
D 5.9 in | 14.9 cm
H 7.4 in | 18.8 cm



Sea Water Membrane

L 46.2 in | 117.3 cm
D 5.2 in | 13.2 cm
H 12.4 in | 31.4 cm



Boost Pump

L 15 in | 38.4 cm
D 6.4 in | 16.3 cm
H 10 in | 25 cm



Remineralizer

L 11.5 in | 29.2 cm
D 5.7 in | 14.5 cm
H 5.7 in | 14.5 cm



Fresh Water Flush

L 11.5 in | 29.2 cm
D 5.7 in | 14.5 cm
H 5.7 in | 14.5 cm



(2) Pre-Filter

L 18.25 in | 46.3 cm
D 5.7 in | 14.5 cm
H 5.7 in | 14.5 cm